* Revised:
3/19/2012

CENTURYLINK REF # E.304938

COUNTY:MORRISON
TWN:129N
RNG:31W
SECT:13

NOTE:
1)ALL PLACING TO BE BY DIRECTIONAL BORE
2)STATE RD CROSSING AT A DEPTH OF 60"
3)COUNTY RD CROSSING AT A DEPTH OF 60"
4)ALL OTHER LOCATIONS AT MINIMUM DEPTH OF 48"

PI. 26+21.7
Δ - 0°21' LT.

STA. 23+75 FE. ENT. LT.
INP. 18" X 16' CMC. REMOVE
F.&I. 15' X 22' SCP.
F.&I. 2 APRONS

MEADOW

STA. 18+15 ℄
INP. 24" X 38' CMC. REMOVE
F.&I. 30" X 38" SCP.
F.&I. 2 APRONS

STA. 13+19 FM. ENT. LT.
INP. 12" X 20' CMC. REMOVE
F.&I. 15" X 22' SCP.
F.&I. 2 APRONS

STA. 12+90 F M. ENT. LT.
INP. 12" X 20' CMC. REMOVE
F.&I. 15" X 22" SCP.
F.&I. 2 APRONS

WOODED PASTURE

WOODED PASTURE

Δ=53½°

ROCK PILE

CULTIVATED

CULTIVATED

STA. 13+26 FE. ENT. RT.
INP. 15" X 16' CMC. REMOVE
F.&I. 15" X 22 SCP.
F.&I. 2 APRONS

#PLACE HAND-HOLE
WITH-IN RR/W
30"x48"x36"

STA. 2+75 FE. ENT. LT.
INP. 10' X 20' CMC. REMOVE
F&I. 15' X 22' SCP.
F.&I. 2 APRONS

PI. 0+00
Δ - 0°28' RT.

STA. 0+30 ℄
INP. 24" X 30' CMC.
DO NOT DISTURB

BEG. SP. 49-523-01
3420(1) STA. 0+00

SAR 3

+ AT OR NEAR 48' FROM C/L

NOTICE:
LOCATE ALL FACILITIES BEFORE DIGGING.
POTHOLE ALL FACILITIES BEFORE CROSSING
RESTORE WHEN COMPLETED TO CO'S SATISFACTION.

PERMIT #2012-129

CL. & GR. 0.05 A. LT.
CL. & GR. 0.30 A. RT.
CL. & GR. 0.05 A. RT.
CL. & GR. 0.05 A. RT.
CL. & GR. 0.05 A. RT.
CL. & GR. 0.05 A. RT.
CL. & GR. 0.05 A. RT.
CL. & GR. 0.05 A. RT.
CL. & GR. 0.05 A. RT.
CL. & GR. 0.05 A. RT.

AD DT. CT. & RT.

STA. 7+00 TO 12+00 SUB EXC. LD BELOW PROFILE GRADE
BEGIN TAPER STA. 6+00 END TAPER STA. 12+60
BACKFILL WITH SELECT MTL. FROM ADJACENT CUTS
QUAN. INCLUDED IN CLASS "C" EXCAVATION

400' VC
M=0.1%

PL 17+00
EL. (22.22)

400' VC
M=0.1%

B.M. EL. 1210.45
SPIKE IN 12" ELM
LT. 8.5' STA. 11+12

INLET 1207.10
OUTLET 1207.10

SURFACE ROCK IIA
EXC. 6991
EMB. 6782

EXC. 1098
EMB. 875

EXC. 1012
EMB. 753

3 ROCK - 2 A1

+016

15' LT.
15' RT.

TH 25 OAK
STA. 7+30 SAR 3

1230
1220
1210
1200

SAR 6
T.H. 25 TO SAR 6

SHEET 5 OF 48

PLATE I - PLAN-PROFILE